



Alumi-Flex™ 302 (18-8) Stainless Steel Drill Screws

For fastening to aluminum when corrosion is a primary concern



Made in the U.S.A.



Stainless steel drill screws provide strength and corrosion resistance in a variety of aluminum applications.

Specifications

- Diameters: #10 to 1/4"
- Lengths: 1/2" to 1-1/2"
- Head Style: Hex washer
- Drive System: Hex
- Point Types: #3 and #4
- Material: 302 stainless steel
- Finish: Stalgard® GB (Galvanic Barrier) coating

Features & Benefits

- Provides a very high level of corrosion resistance
- Coating allows greater galvanic compatibility in dissimilar metal applications involving aluminum
- Head marked with a "3" for easy identification

Catalog No.	Description	Point Type	Finish	Carton Quantity	Carton Weight
#10 Diameter Hex Washer Head					
EAH430	10-16 x 1/2"	#3	Stalgard GB	8,000	51
EAH445	10-16 x 3/4"	#3	Stalgard GB	6,000	46
EAH460	10-16 x 1"	#3	Stalgard GB	5,000	45
#12 Diameter Hex Washer Head					
EAH630	12-14 x 3/4"	#3	Stalgard GB	5,000	40
EAH650	12-14 x 1"	#3	Stalgard GB	5,000	52
EAH680	12-14 x 1-1/2"	#3	Stalgard GB	3,000	44
1/4" Diameter Hex Washer Head					
EAH800	1/4-14 x 3/4"	#3	Stalgard GB	3,500	51
EAH820	1/4-14 x 1"	#3	Stalgard GB	3,000	48
EAH835	1/4-14 x 1-1/2"	#3	Stalgard GB	2,000	41
EAH870	1/4-20 x 1"	#4	Stalgard GB	2,000	35
EAH880	1/4-20 x 1-1/2"	#4	Stalgard GB	2,000	42

Note: For aluminum applications **only**. See previous page for performance data.



Identification

The head marking consists of the number "3" below the Elco® logo as shown to the left.